

TrueBoard 75 inch (4GB/32GB) T29864-A

FEATURES



- Ultra Resolution Output.
- Zero bonding technology for natural writing experience.
- Front audio stereophonic speakers.
- Industrial grade aluminium frame.
- Multiple signal input HDMI, SPDIF, RS232, AV I/O, Earphone.
- Infrared touch technology for rich writing experience.
- Password Lock protected.
- 450 cd/m² ± 5% high brightness.
- Built in Android OS with optional windows 10 OS.
- 4mm protect and anti-scratch glass.
- 20 Point Touch. ≤5ms response.

Android 13



DISPLAY

| | |
|----------------------|---------------------------------------|
| Screen Size | 75" |
| Resolution | 3840 x 2160 |
| Bonding Technology | Zero Bonding |
| Display Orientation | Landscape |
| Screen Type | TFT LCD (Direct-LED Backlight) |
| Blue Light Reduction | Yes |
| Pixel Pitch | 0.4296 (W) x 0.4296 (H) |
| Aspect Ratio | 16:9 |
| Display Area | 1652mm (W) x 930mm (H) (65 x 36.6 in) |
| LCD Viewing Angle | 178° H/V |
| Response | 8ms |
| Refresh Rate | 60Hz |
| LED Lifespan | 60,000* Hours |
| Contrast Ratio | 5000:1 Dynamic, 1200:1 Static |
| Brightness | 450 cd/m ² (±5%) |
| Glass Hardness | 9H (Pencil), 7 (Mohs) |
| Glass Type | Heat tempered, Anti-Glare |

TOUCH FEATURES

| | |
|---------------|--|
| Touch Type | Infrared touch, 20 points touch (Android), 40 points (Windows) |
| Response Time | ≤5ms |
| Touch Object | All Opaque object, such as Finger, pen etc. |

| | |
|------------------|-----------------|
| Touch Resolution | 32768 x 32768px |
| Touch Accuracy | 1mm |
| Tracking Rate | 4m/s |
| Scan Rate | 200Hz |

COMPUTING

| | |
|--------------------------|---|
| Operating System | Android 13 |
| RAM | 4GB |
| Internal Storage | 32GB |
| CPU | Amlogic T982, Quad Core ARM Cortex-A55 CPU, 1.9 GHz |
| GPU | Mali-G52 MP2 (2EE) |
| UI Language | English, Hindi, Gujrati, Kannada, Telgu. |
| | - AV1 MP-10 @L6.0 / 5.1 up to 8K x 4K @30fps or 4K x 2K @60fps |
| | - H.265 HEVC MP-10 @L5.1 up to 8K x 4K @30fps or 4K x 2K @60fps |
| | - VP9 Profile 2 up to 8K x 4K @30fps or 4K x 2K @60fps |
| | - AVS2 MP up to 4K x 2K@60fps |
| | - H.264 AVC HP@L5.1 up to 4Kx2K@30fps |
| | - H.264 MVC up to 1080P@60fps |
| | - MPEG-4 ASP@L5 up to 1080P@60fps |
| | - WMV/VC-1 SP / MP / AP up to 1080P@60fps |
| | - AVS-P16 (AVS+) / AVS-P2 JiZhun Profile up to 1080P@60fps |
| | - MPEG-2 MP / HL up to 1080P@60fps |
| | - MPEG-1 MP / HL up to 1080P@60fps |
| | - Multiple language and multiple format sub-title video support |
| | - MJPEG and JPEG unlimited pixel resolution decoding |
| | - Supports JPEG thumbnail, scaling, rotation and transition effects |
| | - AVS-P16 (AVS+) /AVS-P2 JiZhun Profile up to 1080P@60fps |
| | - Supports *.mkv,*.wmv, *.mpg, *.mpeg, *.dat, *.avi, *.mov, *.iso, *.mp4 and *.jpg file formats |
| Video / Picture Decoding | - Independent JPEG and H.264 encoder with configurable performance / bit-rate |
| | - JPEG image encoding |
| | - H.264 video encoding up to 1080P@30fps with low latency |

SPEAKER

| | |
|----------------------------|---------|
| Dual Front-Facing Speakers | 2 x 20W |
|----------------------------|---------|

NETWORK

| | |
|--------------|-------------------------------|
| LAN in(RJ45) | 10/100Mbps |
| Wake-on-LAN | Yes |
| Wi-Fi | IEEE802.11A/b/g/n/ac,2.4G, 5G |
| Bluetooth | 5.0 |

CONNECTIVITY

| | |
|-----------------------------|----------------------------------|
| HDMI In (Rear) | 2 x HDMI 2.0 version |
| Line In / Mic In (3.5mm) | 1 |
| Line Out / Earphone (3.5mm) | 1 |
| USB-B 3.0 (Rear) | 1 |
| USB-B 2.0 (Rear) | 2 |
| USB-A 2.0 (Touch out Rear) | 1 |
| Smart USB-B 3.0 (Front) | 3 (Both work on Android and OPS) |

| | |
|--------------------------------|----------------------|
| HDMI in (Front) | 1 x HDMI 2.0 version |
| USB-C 2.0 (Type-C Front) | 1 (Work as USB 2.0) |
| USB-A 2.0(Touch Front) | 1 |
| Light Sensor | Yes |
| NFC (Near-field communication) | Optional |

PANEL MANAGEMENT

| | |
|-----------------------------------|---|
| OTA | Yes |
| MDM (Multiple Display Management) | <ul style="list-style-type: none"> • IFPD information (IFPD Location, IP, MAC, Operation System version, Specification etc.) • User management • IFPD Device management (Power on / off, Screen Lock, Sent Message, Program work flow, Setting Parameters, Install / Uninstall APK, Upgrade firmware etc) • Running log • Group management |
| Own APK Store Market | Manage private APK store market |

PHYSICAL SPECIFICATIONS

| | |
|---------------------------------|----------------------------|
| Handle | 2 |
| Panel Net Weight (Kg) | 62 |
| Packed Weight (Kg) | 72 |
| Panel Dimensions (W x H x D)mm | 1717.4mm x 1025mm x 94.9mm |
| Packed Dimensions (W x H x D)mm | 1850mm x 200mm x 1130mm |
| VESA Mount Point mm | 641.6 x 460 |
| Housing | 3 Black 1 Silver |

POWER

| | |
|-------------------------------|-------------------------|
| Power Requirements | 100V ~ 240V AC, 50/60HZ |
| Energy Star Power Consumption | ≤250W (without OPS) |
| Power Consumptions (Standby) | ≤0.5W |
| Ultra-Quiet Fanless Design | Yes |


ENVIROMENTAL

| | |
|-----------------------|------------------------------------|
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Storage Temperature | -15° to 55°C(-5°F to 131°F) |
| Operating Humidity | 20% to 80% non-condensing humidity |
| Storage Humidity | 20% to 90% non-condensing humidity |

PACKED CONTENTS

| | |
|-----|---|
| Kit | 1*IFPD Panel, 1*Remote Controller, 1*Wall Mount Bracket, 2*Stylus, 1*Power Cable, 1*Touch cable |
|-----|---|

TECHNICAL DRAWING



* Note: Product specifications are subject to change without prior notice.